



Z4M™/Z6M™

Thermal, On-demand, Metal Bar Code Printers

The rugged, new Z Series™ metal printers.

The Z4M and Z6M thermal printers have a personality all their own—along with a rugged look and feel characteristic of a Zebra workhorse. These hard workers get the job done in your shipping/receiving, compliance labeling, asset tracking, ticketing, work-in-process, and commercial/small business applications.

Powerful, Price-Performance Leader

Get more bang for your buck! Among Zebra's fastest printers at 10 inches per second, these state-of-the-art metal printers with back-lit LCD control panels work hard, but are easy on your budget.



Connect with it. Count on it.™



Z4M™ / Z6M™

Rugged Construction

- Heavy-gauge steel media and electronics covers
- Die-cast aluminum base, frame and printhead mechanism

Competitively Priced, State-of-the-art Printers

- Price-performance leaders
- More standard features per dollar than any other printers in their class
- Print speeds up to 10 inches per second
- **NEW** ZebraLink™ connectivity and control solution

Simple, Reliable Operation

- Standard back-lit LCD control panel for printer adjustments on the fly
- Printhead with head open lock stays in full open position for convenient media loading
- Full-size media window for easier viewing of your label and ribbon supplies
- Color-coded operator cues, auto-calibration for intuitive operation and quick printer set-up

For more information

Contact your Zebra representative for additional printer specifications. For information on Zebra's other printers, supplies, software and accessories, ask your reseller, call +1 800.423.0442, or visit our Web site.

www.zebra.com



Zebra Technologies Corporation

International Headquarters

333 Corporate Woods Parkway
Vernon Hills, IL 60061-3109 U.S.A.
Phone: +1 847.634.6700 or +1 800.423.0442
Fax: +1 847.913.8766
www.zebra.com

Other Locations

United States: California, Florida, Rhode Island, Wisconsin
Europe: France, Germany, Italy, United Kingdom
Asia-Pacific: Australia, China, Japan, Singapore, South Korea

©2001 Zebra Technologies Corporation
Printed in U.S.A.



Z4M/Z6M
#11218L Rev. 2 (10/01) 20M

Specifications at a Glance*

Standard Features

- Print methods: Thermal transfer or direct thermal
- Construction: Die-cast aluminum base, frame and printhead mechanism
- ZebraLink
- Metal media cover with large clear window
- Zebra E™ Printhead Energy Control
- Auto-calibration
- Auto-detectable power supply
- Color-coded operator cues
- Back-lit LCD control panel

Zebra Programming Language

- ZPL® & ZPL II®—universal language for Zebra printers. Simplifies label formatting and enables seamless compatibility with other Zebra printers.
- ZBI—works with ZPL to control and interpret text and data streams from peripherals and non-ZPL printer programming languages. Transmits captured data over LAN, WAN, or wireless network via e-mail or TCP/IP messaging.

Operating Characteristics

Environment

- Operating Temp. 40°F/5°C to 104°F/40°C
- Storage/Environ. -40°F/-40°C to 140°F/60°C
- Operating Humidity 20-85% non-condensing
- Storage Humidity 5-85% non-condensing

Electrical

- Universal auto-detectable (PFC-compliant) power supply 90-265 VAC; 48-62 Hz; 5A fused

Communication Interface Capabilities

- RS-232C/422/485 serial port
- Bi-directional parallel port

Agency Approvals

- UL 1950; CISPR 22 (Class B); IEC 950; 801-2, -3 and -4 standards; Canadian Doc. (Class A); FCC (Class B); CE compliance

Media Characteristics

Labels

Max. Roll Size

- 8"/203mm O.D. on a 3"/76mm I.D. core
- Thickness (label & liner)
- .0023"/.058mm to .01"/.25mm

Media Types

- Continuous or fanfold, die-cut, notched, tag stock, black mark, perforated

For optimum print quality and printer performance, use Genuine Zebra supplies.

Ribbons

Max. Roll Size

- 3.2"/81.3mm O.D. on a 1"/25.4mm I.D. core

Standard Lengths

- 1476"/450m; provides 3:1 media roll to ribbon ratios

Ribbon Setup

- Ribbon wound ink side out

Ribbon is recommended to be at least as wide as media.

Fonts/Graphics/Symbologies

Fonts and Character Sets

- Standard Fonts: 9 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
- Sets: IBM® Code Page 850 International character set
- Optional European and Asian font sets

Graphic Features

- Supports user-defined fonts and graphics—including custom logos
- ZPL II drawing commands—including boxes and lines

Bar Code Symbologies

- Linear Bar Codes: Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digital extensions, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar
- 2-Dimensional: CODABLOCK, PDF-417, Code 49, DataMatrix, Maxi Code, QR Code, Micro PDF-417

Options and Accessories

- 300dpi printhead
- Up to 2MB (onboard) Flash; up to 8MB additional Flash via PCMCIA
- Cutter with catch tray
- Value peel—a front mount, passive peel option with no liner take-up
- Liner take-up (works with value peel option)—full roll liner take-up spindle (fits standard base; Z4M only)

- Rewind—internally rewinds full label roll on three-inch core (comes with taller, non-standard printer base)
- PCMCIA connector (supports PC cards up to 8MB)
- ZebraNet PrintServer II (external)
- BAR-ONE® software
- European and Asian font sets



Z 4 M

Z 6 M

The rugged Z4M/Z6M metal printers are ideal for a wide variety of applications, including:

- Shipping/Receiving
- Compliance labeling
- Asset tracking
- Ticketing
- Work-in-process
- Commercial/Small business

Maximum Print Area (standard memory)

Z4M

Width: 4.09"/104mm

Length with 203dpi:

105"/2,667mm

Length with 300dpi:

49"/1,245mm

Z6M

Width: 6.6"/168mm

Length with 203dpi:

65"/1,651mm

Length with 300dpi:

29"/737mm

Physical Characteristics

Z4M

Width: 10.93"/278mm

Depth: 18.69"/475mm

Height: 13.32"/338mm

Weight: 32.4lbs/15kg

Z6M

Width: 13.43"/341mm

Depth: 18.69"/475mm

Height: 13.32"/338mm

Weight: 34.7lbs/16kg

Media Specifications

Z4M

Label and liner width:

1"/25.4mm–

4.5"/114mm

Ribbon width:

2"/51mm–

4.33"/110mm

Z6M

Label and liner width:

2"/51mm–

7"/178mm

Ribbon width:

2"/51mm–

6.85"/174mm

Resolutions

203dpi/8dots per mm; 300dpi/12dots per mm

Maximum Print Speed

10"/254mm per second (with 203dpi)

Memory

Standard: 4MB DRAM (2MB user available)

Optional: Up to 2MB (onboard) Flash; up to 8MB additional Flash via PCMCIA

ZebraLink™

ZebraLink, a revolutionary real-time connectivity and control solution for Zebra printers, includes:

1. **Alert** (with ZebraNet® PrintServer II)—enables a Zebra printer to send unsolicited Alert condition messages via email-enabled tools.
2. **WebView** (with ZebraNet PrintServer II)—enables the remote monitoring and configuration capability of Zebra printers in real-time using Web-based network tools.
3. **ZBI** (Zebra BASIC Interpreter)—programming language that works with ZPL II to control and interpret incoming text and data.



FMC-32328
An ISO 9001 registered company

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.



Test drive it today at
www.zebra.com/livelink